

GUNFIRE

ballistic spectacles - kit

The ideal kit for shooting enthusiasts.

STANAG 4296 & EN172 certified, the GUNFIRE comes with interchangeable temples (black / red - black / gray) & a mono lens system. Clear version or CSP (indoor / outdoor), the GUNFIRE has the exclusive

PLATINUM antifog and anti-scratch coating as standard.

Supplied in a rigid case complete with a microfiber pouch.





PLATINUM (P)

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant, durable and delays the appearance of fogging.

6CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM coating that combats fogging.



GUNFIRE KIT









The GUNFIRE KIT is supplied with 2 spare lenses (clear and CSP), 2 sets of temples, a microfibre pouch and a rigid case.



GUNFIRE

ballistic spectacles - kit

markings / standards

Model	Reference	Version	Lens marking	Frame marking	V50 Ballistic resistance STANAG 4296	ANSI/MIL	Coatings
GUNFIRE	GUNFIREKIT	 Clear	2C-1,2  1 FT KN C€	 EN166 FT C€	853,2 km/h - 237 m/s	ANSI Z87.1-2010 MIL-PRF-32432	 PLATINUM (P)
		 CSP	5-1,4  1 FT KN C€	 EN166 FT C€	871,2 km/h - 242 m/s	ANSI Z87.1-2010 MIL-PRF-32432	 PLATINUM (P)

CHARACTERISTICS

LENS: PC - 2.2 mm - curve 10
PLATINUM coating. Interchangeable lenses.

CHARACTERISTICS

TEMPLES: Comfortable and interchangeable
bi-material temples available in 2 colors
grey/black or red/black.

WEIGHT: 26 g - 212g for the whole kit

packaging and ean13 code :

Model	Reference	Unit	Inner box	Units	Outer box	Units
GUNFIRE	GUNFIREKIT	3660740007843	X	X	3660740107840	x 51

Notified laboratories for certification:



12/04/2017