

SWAT

ballistic sunglasses

STANAG 2920 and EN172 certified, these SWAT ballistic protection sunglasses ensure maximum protection against any event. Thanks to its non-slip bridge, its flexible temples and its ultra enveloping design, SWAT will provide you with comfort and protection. SWAT is available in **smoke**  **PLATINUM**, **silver mirror coated** and **polarized versions**.

ULTRA FLEXIBLE AND COMFORTABLE FRAME

BALLISTIC POLYCARBONATE LENS

(NEW)

 **PLATINUM COATING**

ON SMOKE VERSION



NON-SLIP BRIDGE

INTEGRATED LATERAL PROTECTION

COMFORTABLE NON SLIP TEMPLES



 **PLATINUM (P)**

The new exclusive PLATINUM coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.



VERSIONS AVAILABLE :



SWATFLASH



SWATPSF




SWATPOL

SUPPLIED WITH :



Supplied with microfibre pouch and individual soft carry case



SWAT

ballistic sunglasses

markings / norms

Model	Reference	Version	Lens markings	Frame marking	V50 Ballistic Resistance STANAG 2920	ANSI/MIL	Coatings
SWAT	SWATPSF	 Smoke	5-3.1 ☞ 1 FT KN CE	☞ EN166 FT CE	705 km/h - 196 m/s	ANSIZ87.1-2010	PLATINUM (P)
	SWATFLASH	 Silver flash	5-3.1 ☞ 1 FT CE	☞ EN166 FT CE	655 km/h - 182 m/s	ANSIZ87.1-2010	ASAF
	SWATPOL	 POLARIZED	5-3.1 ☞ 1 FT CE	☞ EN166 FT CE	659 km/h - 183 m/s	ANSIZ87.1-2010	ASAF

CHARACTERISTICS

LENS:

Ballistic PC lens - 2.2 mm - Base 8
 PLATINUM coating (on smoke version)
 Integrated lateral protection

CHARACTERISTICS

TEMPLES:

Comfort bi-material (Nylon + PVC)
 non-slip temples

FRAME: Available in shiny black

WEIGHT: 28 g

**HIGH
RESISTANCE**

packaging and ean13 code :

Model	Reference	Unit	Inner box	Units	Outer box	Units
SWAT	SWATPSF	3660740000677	X	X	3660740200671	x 95
	SWATFLASH	3660740000684	X	X	3660740200688	x 95
	SWATPOL	3660740000691	X	X	3660740200695	x 95

Notified laboratories for certification:



06/03/2015